

# Gavita Pro 6/750<sup>e</sup> DE FLEX AUS



## General product information

Product name:	Gavita Pro 6/750 <sup>e</sup> DE FLEX AUS
Manufacturer:	Gavita International bv
Version:	240 V AUS
Part number:	18.30.74.23.60

## Compatible products and accessories

	Product name	Gavita part number
Controllers:	Gavita Master Controller EL1	41.00.24.60
	Gavita Master Controller EL2	41.00.25.60
Reflector:	Gavita Pro HR 96 DE reflector	31.46.13.00
	Gavita Pro W 150 DE reflector	31.26.13.00
	Gavita Pro M 110 DE SR reflector	30.27.13.00
Lamps:	Gavita Pro 750W EL DE HPS	26.74.19.11
Power cords:	Power cord AUS 240 V, 16 ft / 5 meter	44.30.41.08
	Power cord AUS 240 V, 8 ft / 2,5 meter	44.30.41.12
Interconnect cables:	Interconnect cable RJ14, 2 ft / 0,6 meter	43.50.00.08
	Interconnect cable RJ14, 8 ft / 2,4 meter	43.50.00.09
	Interconnect cable RJ14, 10 ft / 3 meter	43.50.00.10
Iplitter:	3 way RJ14 cable splitter	43.50.00.01

## Technical specifications

Product name:	Gavita Pro 6/750 <sup>e</sup> DE FLEX AUS
Input voltage +/- 10%:	240 Volt AC
Frequency:	50 - 60 Hz
Input current at 100%:	3.5 Amps
Input current at 110%:	3.9 Amps
Input power at 100%:	795 Watt
Input power at 110%:	870 Watt
Inrush current:	40 Amps
Power factor:	0.97 - 0.99
Product weight:	5.6 kg
Dimensions (LxWxH):	23"x 9.5"x 11.5" (56,5x24.5x22.5cm)
Temperature ambient:	0-35 °C
Relative humidity:	<70%
Total Harmonic Distortion:	<10%
Power inlet:	IEC C14
External dim connector	RJ14 (6p4c)

## Legislation

CE LVD approval according to: EN 60598-1: 2008 + A11: 2009.

CE EMC approval according to: EN 55015 (2006) + A1 (2007) + A2 (2009); EN 61000-3-2 (2006) + A1 (2009) + A2 (2009); EN 61000-3-3 (2008); EN 61547 (2009).

## Included accessories

User manual, power cord, 2 RJ14 controller cables and a T-splitter for plug and play installation, Gavita Pro lamp.